





Cut Out
75mm

Beam Angle
15° 24° 36°


Power
8/10W



Item No.: 187500A
Power: 8/10W
Ra: 95
CCT: 2700/3000/3500/4000K
Light efficacy: 80~85lm/W
LED & Driver: SANAN + Lifud/Eaglerise
IP: IP40
Size: ϕ 85*H96mm
Cut out: ϕ 75mm



Item No.: 187510A
Power: 8/10W
Ra: 95
CCT: 2700/3000/3500/4000K
Light efficacy: 80~85lm/W
LED & Driver: SANAN + Lifud/Eaglerise
IP: IP40
Size: ϕ 85*H96mm
Cut out: ϕ 75mm



Item No.: 187570
Power: 8/10W
Ra: 95
CCT: 2700/3000/3500/4000K
Light efficacy: 80~85lm/W
LED & Driver: SANAN + Lifud/Eaglerise
IP: IP40
Size: ϕ 85*H88mm
Cut out: ϕ 75mm



Item No.: 187580
Power: 8/10W
Ra: 95
CCT: 2700/3000/3500/4000K
Light efficacy: 80~85lm/W
LED & Driver: SANAN + Lifud/Eaglerise
IP: IP40
Size: ϕ 85*H88mm
Cut out: ϕ 75mm



Item No.: 187550C
Power: 8/10W
Ra: 95
CCT: 2700/3000/3500/4000K
Light efficacy: 80~85lm/W
LED & Driver: SANAN + Lifud/Eaglerise
IP: IP40
Size: ϕ 85*H99mm
Cut out: ϕ 75mm



Item No.: 187560C
Power: 8/10W
Ra: 95
CCT: 2700/3000/3500/4000K
Light efficacy: 80~85lm/W
LED & Driver: SANAN + Lifud/Eaglerise
IP: IP40
Size: ϕ 85*H99mm
Cut out: ϕ 75mm



Cut Out
55mm

Beam Angle
15° 24° 36°

Power
6W



Item No.: 186500A
Power: 6W
Ra: 95
CCT: 2700/3000/3500/4000K
Light efficacy: 80~85lm/W
LED & Driver: SANAN + Lifud/Eaglerise
IP: IP40
Size: ϕ 65*H83mm
Cut out: ϕ 55mm




Item No.: 186510A
Power: 6W
Ra: 95
CCT: 2700/3000/3500/4000K
Light efficacy: 80~85lm/W
LED & Driver: SANAN + Lifud/Eaglerise
IP: IP40
Size: ϕ 65*H83mm
Cut out: ϕ 55mm



Item No.: 186550C
Power: 6W
Ra: 95
CCT: 2700/3000/3500/4000K
Light efficacy: 80~85lm/W
LED & Driver: SANAN + Lifud/Eaglerise
IP: IP40
Size: ϕ 65*H86mm
Cut out: ϕ 55mm



Item No.: 186560C
Power: 6W
Ra: 80/90
CCT: 2700/3000/3500/4000K
Light efficacy: 80~85lm/W
LED & Driver: SANAN + Lifud/Eaglerise
IP: IP40
Size: ϕ 65*H86mm
Cut out: ϕ 55mm



Item No.: 186570
Power: 6W
Ra: 95
CCT: 2700/3000/3500/4000K
Light efficacy: 80~85lm/W
LED & Driver: SANAN + Lifud/Eaglerise
IP: IP40
Size: ϕ 62*H83mm
Cut out: ϕ 55mm



Item No.: 186580
Power: 6W
Ra: 95
CCT: 2700/3000/3500/4000K
Light efficacy: 80~85lm/W
LED & Driver: SANAN + Lifud/Eaglerise
IP: IP40
Size: ϕ 62*H83mm
Cut out: ϕ 55mm




Item No.: 186595C
Power: 6W
Ra: 95
CCT: 2700/3000/3500/4000K
Light efficacy: 80~85lm/W
LED & Driver: SANAN + Lifud/Eaglerise
IP: IP40
Size: ϕ 62*H91mm
Cut out: ϕ 55mm




Cut Out
30~50mm

Beam Angle
15° 24° 36°


Power
3W



Item No.: D3003
Power: 3W
Ra: 80/90
CCT: 2700/3000/3500/4000K
Light efficacy: 80~85lm/W
LED & Driver: CREE + Eaglerise
IP: IP40
Size: ϕ 35*H42mm
Cut out: ϕ 30mm



Item No.: D4003
Power: 3W
Ra: 80/90
CCT: 2700/3000/3500/4000K
Light efficacy: 80~85lm/W
LED & Driver: CREE + Eaglerise
IP: IP40
Size: ϕ 45*H46mm
Cut out: ϕ 40mm



Item No.: D5003
Power: 3W
Ra: 80/90
CCT: 2700/3000/3500/4000K
Light efficacy: 80~85lm/W
LED & Driver: CREE + Eaglerise
IP: IP40
Size: ϕ 55*H59mm
Cut out: ϕ 50mm

